

▶ 儿童口罩机

CHILDREN'S MASK MAKING MACHINE

该设备实现儿童平面式耳带口罩自动化生产, 包含上料、折叠压合、鼻梁筋上料、口罩成型、耳带焊接、成品下料等制作工艺, 完成口罩自动化生产。

The equipment realizes the automatic production of children's flat earband masks, including the production process of feeding, folding and pressing, noseband feeding, mask forming, earband welding, finished product discharging, etc., to complete the automatic production of masks.



■ 产品参数 / PRODUCT PARAMETERS


儿童口罩机 / Children's mask making machine	
设备尺寸 / Size	5000mm (L) ×2500mm (W) ×2000mm (H)
外观颜色 / Color	国际标准暖灰1C / International standard warm gray 1C
设备重量 / Weight	≤1500kg, 地面承重 (Floor load-bearing) ≤300kg/m²
工作电源 / Power supply	220VAC±5%; 50HZ; 额定功率 (Power Rating) 12KW
工作气压 / Air pressure	压缩气压力(Compressed gas pressure)0.5—0.8MPa; 压缩气流量(Compressed gas flow)300L/min
生产效率 / Efficiency	100—110PPM
生产合格率 / Qualified rate	99%
设备故障率 / Malfunctioning rate	≤2%
使用环境 / Using environment	温度: 10—35℃; 湿度: 5—35%HR, 无可燃性、腐蚀性气体、无粉尘(洁净度不低于10万级) Temperature: 10-35℃; Humidity: 5-35%HR, no combustible, no corrosive gas, no dust (cleanliness not less than 100,000 levels)

▶ 一拖一平面口罩机

ONE PLANE MASK MAKING MACHINE

该设备实现平面式耳带口罩自动化生产, 包含上料、折叠压合、鼻梁筋上料、口罩成型、耳带焊接、成品下料等制作工艺, 完成口罩自动化生产。生产的口罩佩戴舒适, 无压迫感, 可用于工厂生产, 医院医疗, 建筑施工, 日常生活等场景。

This machine realizes the automatic production of flat type ear band masks, including the production process of loading, folding and pressing, nasal band loading, mask forming, ear band welding, and finished product discharging, etc., to complete the automatic production of masks. The masks produced are comfortable to wear, no pressure, and can be used in factory production, hospital medical, construction, daily life and other scenes.



■ 产品参数 / PRODUCT PARAMETERS

一拖一平面口罩机 / One plane mask making machine	
设备尺寸 / Size	5000mm (L) ×2500mm (W) ×2000mm (H)
外观颜色 / Color	暖白+银白 / Warm White + Silvery White
设备重量 / Weight	≤1500kg, 地面承重 (Floor load-bearing) >300kg/m²
工作电源 / Power supply	220VAC±5%; 50HZ; 额定功率 (Power Rating) 10KW
工作气压 / Air pressure	压缩气压力(Compressed gas pressure)0.5—0.8MPa; 压缩气流量(Compressed gas flow)420L/min
生产效率 / Efficiency	≥100PPM
生产合格率 / Qualified rate	99%
设备故障率 / Malfunctioning rate	≤2%
使用环境 / Using environment	温度: 10—35℃; 湿度: 5—35%HR, 无可燃性、腐蚀性气体、无粉尘(洁净度不低于10万级) Temperature: 10-35℃; Humidity: 5-35%HR, no combustible, no corrosive gas, no dust (cleanliness not less than 100,000 levels)

